Amendments to the Claims:

1. (currently amended) A processor comprising:

~~a central processing unit (CPU) processing data according to an instruction set;~~

a data memory for storing non-stack data;

a stack memory for storing stack data, where the stack memory is different from the data memory;

a memory address generator coupled to the data memory for producing addresses to~~for~~ access~~ing~~ the data memory; ~~and~~

a stack pointer generator coupled to the stack memory for producing a stack pointers ~~for accessing~~to access the stack memory~~.~~; and

a central processing unit (CPU) coupled to the memory address generator and the stack pointer generator, the central processing unit for processing non-stack data and stack data according to an instruction set;

wherein the stack pointer generator is further for producing a software stack pointer to access the stack memory when passing parameters to subroutines of the central processing unit.

2. (currently amended) The processor of claim 1 wherein the processor is a ~~Micro-Computer System (MCS) series processor~~microcontroller.

3. (original) The processor of claim 1 wherein the processor processes an 8-bit instruction set.

4. (original) The processor of claim 3 wherein the data memory is 256 bytes.

5. (original) The processor of claim 3 wherein the stack memory is 256 bytes.

6. (new) The processor of claim 1 wherein the stack pointer generator is further for incrementally increasing the stack pointer to point to a next address when used by

the central processing unit, and for decreasing the software stack pointer from a predetermined starting position when passing parameters to subroutines of the central processing unit.

7. (new) A method for providing a processor with unshared stack memory, the method comprising:
providing a data memory for storing non-stack data;
providing a stack memory for storing stack data;
producing addresses to access the data memory;
producing a stack pointer for accessing the stack memory;
providing a central processing unit (CPU) for processing non-stack data and stack data according to an instruction set; and
producing a software stack pointer to access the stack memory when passing parameters to subroutines of the central processing unit.

8. (new) The method of claim 7 wherein the processor is a microcontroller.

9. (new) The method of claim 7 further comprising the processor processing an 8-bit instruction set.

10. (new) The method of claim 9 further comprising the data memory being 256 bytes.

11. (new) The method of claim 9 further comprising the stack memory being 256 bytes.

12. (new) The method of claim 7 further comprising increasing the stack pointer incrementally to point to a next address when used by the central processing unit, and decreasing the software stack pointer from a predetermined starting position when passing parameters to subroutines of the central processing unit.